



**ALLIANCE  
AGRICULTURE**

TRA: **R-1**  
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

**Bias R-1 - 16.9-38**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	
16.9-38	W15L	430	1689	770	5007	8PR	1	4350	2840	2320	2020	1890	
							1.2	4830	3150	2580	2250	2100	
							141A8	1.4	5290	3450	2830	2460	2300
								1.7	5920	3860	3170	2760	2575
						12PR	1.9	5890	3840	3150	2740	2560	
							146A8	2.1	6230	4070	3330	2900	2710
								2.3	6580	4290	3520	3060	2860
								2.5	6900	4500	3690	3210	3000

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed Application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
16.9-38	W15Lx38 W14L	430	1689	770	5007	8PR 141A8	0.8	3820	2320	1990	1780	1660	1490
							1	4350	2650	2270	2020	1890	1700
							1.4	5290	3220	2760	2460	2300	2070
							1.7	5920	3860	3170	2760	2575	2320

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

