



**ALLIANCE  
AGRICULTURE**

TRA: **R-1**  
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

**Bias R-1 - 14.9-28**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
14.9-28	W13	378	1365	640	4180	8PR	1.8	4370	2850	2340	2030	1900	1730
						130A8							
						12PR	1	3110	2030	1660	1440	1350	1230
						138A8							
						2	4650	3030	2480	2160	2020	1840	
							2.6	5430	3540	2900	2530	2360	2150

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed Application					
Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph								
14.9-28	W13x28 W12 W11	378	1365	640	4180	8PR	0.8	2710	1650	1420	1260	1180	1060
						130A8	1	3110	1890	1620	1440	1350	1220
							1.4	3770	2300	1970	1750	1640	1480
							1.8	4370	2850	2340	2030	1900	1710

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

