



**ALLIANCE  
AGRICULTURE**

TRA: **R-1W**  
Speed Rating: **A8**



STEEL  
BELTED



STUBBLE  
GUARD

The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

**TRACTOR RADIAL HIGH SPEED - VF 520/85R42 CFO**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
								CFO		Not high and sustained torque; Road transport				
		15 kmph	30 kmph	10 kmph	15 kmph	20 kmph	25 kmph	70 kmph						
VF 520/85R42 CFO	DW16L DW18L	540	1955	874	5806	177A8	0.8	4828	4029	3890	3630	3630	3630	3300
							1.2	6211	5184	5000	4670	4670	4670	4250
							1.6	7594	6338	6120	5710	5710	5710	5200
							2	8326	6949	6710	6260	6260	6260	5700
							2.4	8871	7404	7150	6670	6670	6670	6070
							2.8	9709	8103	7820	7300	7300	7300	6640

Highlighted column indicates speed limit 25kmph to 65kmph

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

