



**ALLIANCE
AGRICULTURE**

TRA: **R-1W**
Speed Rating: **D**



STUBBLE
GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

70 Series - 710/70R42

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
710/70R42	DW23Bx42 DW25B	720	2061	952	6202	173D	0.8	8170	5330	4210	4080	3890	3730	3550
							1.2	10350	6750	5330	5180	4930	4730	4500
							1.6	12880	8400	6640	6440	6130	5880	5600
							2	14150	9230	7290	7070	6730	6460	6150
							2.4	14950	9750	7700	7480	7120	6830	6500

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

