



**ALLIANCE  
AGRICULTURE**

TRA: **R-1W**  
Speed Rating: **D**



STUBBLE  
GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

**70 Series - 480/70R30**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
480/70R30	W15Lx30 W14L W16L	482	1480	663	4412	141D	0.8	3800	2480	1960	1900	1810	1730	1650
							1	4370	2850	2250	2190	2080	2000	1900
							1.2	4880	3180	2510	2440	2320	2230	2120
							1.4	5430	3540	2800	2710	2580	2480	2360
							1.6	5920	3860	3050	2960	2820	2700	2575
	150D	0.8	3800	2480	1960	1900	1810	1730	1650					
		1.3	5150	3360	2650	2580	2450	2350	2240					
		1.8	6270	4090	3230	3130	2980	2860	2725					
		2.3	7070	4610	3640	3540	3370	3230	3075					
		2.8	7710	5030	3970	3850	3670	3520	3350					

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

