

**MAXAM**

# MS702

## INDUSTRIAL STR

Applications:



Premium 2-stage solid resilient tire.

- Premium natural rubber compounds: Compounds do not contain crumb rubber or other fill materials
- Cut and Tear resistant tread
- Chunk Resistant, Non-Marking (NM)
- Premium nylon reinforced base compound
- 2-Stage compound construction with steel torque rings
- Excellent stability
- Deep tread configuration for superior traction
- Available in both Standard, and Swift (Clip/Halo/LOC) bead set configuration



Size	Rim	Type		O.D. mm inch	S.W. mm inch	T.D. mm inch	Load Capacity (kg) Forklift up to 25 km/h	
		STD	Swift				Load Wheels	Steer Wheels
100/80-8 SM	2.50C	*		363 14.3	109 4.3	23 29/32	1000	770
15x4 1/2-8 RIB (125/75-8)	2.50C	*		374 14.7	106 4.2	28 35/32	1040	800
15x4 1/2-8 RIB (125/75-8)	3.00D	*	*	374 14.7	106 4.2	28 35/32	1040	800
15x4 1/2-8 (125/75-8)	3.00D	*	*	374 14.7	106 4.2	28 35/32	1040	800
15x4 1/2-8 (125/75-8)	3.25I	*		374 14.7	106 4.2	28 35/32	1040	800
400-8 RIB	3.00D	*	*	402 15.8	98 3.9	36 45/32	950	730
400-8	3.00D	*	*	402 15.8	98 3.9	36 45/32	950	730
16x6-8	4.33R	*	*	409 16.1	139 5.5	30 38/32	1455	1120
18x7-8	4.33R	*	*	448 17.6	156 5.7	38 48/32	2145	1650
5.00-8	3.00D	*	*	450 17.7	114 4.5	36 45/32	1415	1090
140/55-9	4.00E	*	*	372 14.6	122 4.8	28 35/32	1170	900
21x8-9	6.00E	*	*	514 20.2	178 7.0	51 64/32	2755	2120
6.00-9 RIB	4.00E	*	*	520 20.5	132 5.2	41 51/32	1885	1450
6.00-9	4.00E	*	*	520 20.5	132 5.2	41 51/32	1885	1450
200/50-10	6.50F	*	*	451 17.8	183 7.2	41 51/32	2470	1900
6.50-10	5.00F	*	*	566 22.3	152 6.0	51 64/32	2340	1800
23x9-10 (225/ 75-10)	6.50F	*	*	574 22.6	188 7.4	56 70/32	3445	2650
7.00-12	5.00S	*	*	646 25.4	163 6.4	53 67/32	2920	2240
27x10-12	8.00G	*	*	670 26.4	235 9.3	56 70/32	3900	3000
28x9-15 (8.15-15)	7.00	*	*	682 26.9	202 8.0	51 64/32	3900	3000
250-15 (250/ 70-15)	7.00	*	*	711 28.0	208 8.2	53 67/32	4640	3570
250-15 (250/ 70-15)	7.50	*	*	711 28.0	208 8.2	53 67/32	4640	3570
7.00-15	5.50	*	*	719 28.3	168 6.6	56 70/32	3545	2725
7.50-15	5.50	*	*	748 29.4	187 7.4	58 74/32	3900	3000
7.50-15	6.50	*	*	748 29.4	187 7.4	58 74/32	3900	3000
8.25-15	5.50	*	*	804 31.7	194 7.6	71 90/32	4530	3485
8.25-15	6.50	*	*	804 31.7	194 7.6	71 90/32	4750	3650
300-15 (315/70-15)	8.00	*	*	807 31.8	242 9.5	63 80/32	5850	4500
350-15 (355/65-15)	9.75	*	*	812 32.0	292 11.5	89 112/32	7800	6000
10.00-20	7.00	*		1025 40.4	250 9.8	79 99/32	6000	5000
10.00-20	7.50	*		1025 40.4	250 9.8	79 99/32	6000	5000
10.00-20	8.00	*		1025 40.4	250 9.8	79 99/32	6000	5000
12.00-20	8.00	*		1085 42.7	278 10.9	86 109/32	7650	6300
12.00-20	8.50	*		1085 42.7	278 10.9	86 109/32	7650	6300
12.00-20	10.00	*		1085 42.7	278 10.9	86 109/32	7650	6300

