

**MAXAM**

# MS906

**SKID STEER**

Deep R4 tread pattern designed for skid steer, backhoe and telehandler applications.

- Full flat profile with self-cleaning stepped tread improves performance
- Deep undertread for improved puncture resistance
- Special cut resistant compound improves wear and reduces chunking

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	L.I.	Infl. P.	Load Capacity
				mm inch	mm inch	mm inch		kPa psi	10 km/h 5 mph
5.70-12	6	TL	4.50	569	145	14.0	93A2	415	650
				22.4	5.7	18/32		60	1430
23x8.50-12	6	TL	7JA	583	214	13.3	101A2	340	825
				22.9	8.5	17/32		50	1820
	8	TL	7JA	583	214	13.3	107A2	450	975
				22.9	8.5	17/32		65	2150
12	TL	7JA	583	214	13.3	115A2	515	1215	
			22.9	8.5	17/32		75	2680	
27x8.50-15	8	TL	7JA	682	221	14.0	118A2	415	1320
				26.9	8.7	18/32		60	2910
27x10-12	14	TL	8.00G	701	264	19.0	143A5	690	2725
				27.6	10.4	24/32		100	7800
7.00-15	6	TL	5.50	760	198	16.0	121A2	415	1450
				29.9	7.8	21/32		60	3200
8	TL	5.50	760	198	16.0	125A2	480	1650	
			29.9	7.8	21/32		70	3640	
31x15.50-15	8	TL	13LB	787.0	384	23.0	132A2	310	2000
				31.0	15.1	30/32		45	4400
10-16.5	10	TL	8.25	768	271	16.0	134A2	515	2120
				30.2	10.7	21/32		75	4680
12-16.5	12	TL	9.75	834	331	20.0	145A2	550	2900
				32.8	13.0	25/32		80	6400
14-17.5	14	TL	10.50	920	360	26.0	155A2	550	3875
				36.2	14.2	33/32		80	8550
15-19.5	14	TL	11.75	1020	389	26.0	161A2	480	4625
				40.2	15.3	33/32		70	10200
16	TL	11.75	1020	389	26.0	164A2	550	5000	
			40.2	15.3	33/32		80	11000	

