




**ALLIANCE
AGRICULTURE**

TRA: I-3
Speed Rating: D



Alliance 380 Heavy Duty Flotation tire provides full soil protection and flotation tire characteristics in field. The tires high-speed steel belted radial flotation construction, combined with specific casings construction and special rubber compound enables it to run at high speed on road. Deep non-directional lug type pattern enables high mobility in field including significant traction ability as well as comfortable smooth run on road. Heavy duty tires are best suited for tough applications compared to the standard range.

HEAVY DUTY FLOTATION - 750/45R22.5 Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load										
								Speed										
								Mixed Application										
		SW inch	OD inch					Static mph	6 mph	9 mph	12 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph
750/45R22.5 Steel Belted	AG24.00	29.3	49.2	21.9	151.3	176D	12	12680	9920	NA	NA	8710	8330	7500	6680	5910	5510	NA
							17	16070	12590	NA	NA	11050	10560	9500	8470	7470	6990	NA
							22	18300	14330	NA	NA	12570	12020	10830	9630	8510	7960	NA
							23	19030	14880	NA	NA	13070	12480	11240	10010	8840	8270	NA
							29	21650	16950	NA	NA	14880	14220	12810	11400	10080	9410	NA
							35	24100	18850	NA	NA	16560	15810	14240	12680	11200	10470	NA
							41	26370	20640	NA	NA	18120	17310	15590	13870	12260	11460	NA
							46	28510	22310	NA	NA	19580	18720	16840	14990	13250	12390	NA
							52	30530	23900	NA	NA	20970	20040	18060	16050	14200	13270	NA
							58	32450	25400	NA	NA	22290	21300	19180	17060	15100	14110	NA
						64	34330	26870	NA	NA	23590	22530	20310	18060	15960	14930	NA	
						73	34330	26870	NA	NA	23590	22530	20310	18060	15960	15340	NA	
						87	36000	28180	NA	NA	24740	23630	21300	18940	16760	15650	NA	
						177D 174E	12	12680	9920	9550	9110	8710	8330	7500	6680	5910	5510	5030
							17	16070	12590	12080	11530	11050	10560	9500	8470	7470	6990	6350
							22	18300	14330	13780	13140	12570	12020	10830	9630	8510	7960	7250
							23	19030	14880	14310	13650	13070	12480	11240	10010	8840	8270	7520
							29	21650	16950	16290	15540	14880	14220	12810	11400	10080	9410	8580
							35	24100	18850	18120	17280	16560	15810	14240	12680	11200	10470	9520
							41	26370	20640	19840	18920	18120	17310	15590	13870	12260	11460	10430
46	28510	22310	21430	20440	19580		18720	16840	14990	13250	12390	11270						
52	30530	23900	22950	21890	20970		20040	18060	16050	14200	13270	12080						
58	32450	25400	24410	23280	22290		21300	19180	17060	15100	14110	12830						
64	34330	26870	25820	24630	23590	22530	20310	18060	15960	14930	13580							
73	37020	28970	27840	26570	25420	24300	21890	19470	17220	16090	14640							

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

