



**ALLIANCE  
AGRICULTURE**

TRA: **R-1W**  
Speed Rating: **D**



STUBBLE  
GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

**70 Series - 380/70R20**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
380/70R20	W12x20 W11 W13	382	1086	493	3252	122D	0.8	2190	1430	1130	1090	1040	1000	950
							1	2510	1640	1290	1250	1190	1140	1090
							1.2	2880	1880	1480	1440	1370	1310	1250
							1.4	3130	2040	1610	1560	1490	1430	1360
							1.6	3450	2250	1780	1730	1640	1580	1500

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann  
Chief Technology Officer

