



**ALLIANCE
AGRICULTURE**

TRA: **R-1W**
Speed Rating: **D**



STUBBLE
GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

70 Series - 600/70R28

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
600/70R28	DW20Bx28 DW18L W18L	614	1555	708.6	4652	161D	0.8	5290	3450	2730	2650	2520	2420	2300
							1.3	7070	4610	3640	3540	3370	3230	3075
							1.8	8630	5630	4440	4310	4110	3940	3750
							2.3	9780	6380	5040	4890	4650	4460	4250
							2.8	10640	6940	5480	5320	5060	4860	4625

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

